Tolomatic™
EXCELLENCE *IN MOTION*

ERD ELECTRIC ROD-STYLE ACTUATOR

ENDURANCE TECHNOLOGY℠
A Tolomatic Design Principle



LINEAR SOLUTIONS MADE EASY

ERD – Electric Rod-Style Actuator

The ERD is an economical rod-style electric actuator designed as an alternative to pneumatic cylinders, a cost effective actuator for general automation and an option for automating manual processes. In addition, the ERD is available with all stainless steel and IP69K options which makes it the ideal hygienic actuator for the food & beverage processing environment.



TOLOMATIC'S ELECTRIC ROD-STYLE ACTUATORS

						Combined Actuator & Motor	
	ERD	**RSH**	**RSA**	**RSX**	**GSA**	**IMA**	**IMAS**
							
	Rod-Style Actuator	**Hygienic Rod-Style Actuator**	**Rod-Style Actuator**	**High Force Rod-Style Actuator**	**Guided Rod-Style Actuator**	**Integrated Servo Actuator**	**Hygienic Integrated Servo Actuator**
Force up to:	2 kN *(500 lbf)*	35 kN *(7,900 lbf)*	58 kN *(13,000 lbf)*	445 kN *(100,000 lbf)*	18 kN *(4,100 lbf)*	36 kN *(8,000 lbf)*	11 kN *(2,500 lbf)*
Speed up to:	1.0 m/s *(40 in/s)*	0.5 m/s *(20 in/s)*	3.1 m/s *(120 in/s)*	0.8 m/s *(30 in/s)*	3.1 m/s *(120 in/s)*	1.3 m/s *(50 in/s)*	0.5 m/s *(20 in/s)*
Stroke Length up to:	0.6 m *(24 in)*	1.2 m *(48 in)*	1.5 m *(60 in)*	1.5 m *(59 in)*	0.9 m *(36 in)*	0.5 m *(18 in)*	0.5 m *(18 in)*
Screw/Nut Type	Ball	Ball & Roller	Solid, Ball & Roller	Ball & Roller	Solid, Ball & Roller	Ball & Roller	Ball & Roller
	For complete information see www.tolomatic.com or literature number:						
Literature Number:	2190-4000	2100-4010	3600-4233	2171-4001	3600-4231	2700-4000	2700-4014

(Actuators typically can't achieve maximum force and speed simultaneously. Some options may limit maximum specifications. See product brochure for details.)

ERD – Applications

Gating, Sorting, Diverting



Optional all stainless-steel design for wash-down environments

Aligning



Product Change Over



Heat Staking, Sonic Welding



Other Applications:

- Aligning
- Animation
- Assembly
- Automatic tool changers
- Automotive
- Converting
- Conveyors
- Diverting
- Fillers
- Formers
- Gating
- Heat staking
- Laser positioning
- Material handling systems
- Medical equipment
- Motion simulators
- Open/close doors
- Packaging equipment
- Parts clamping
- Patient lifts
- Pick & place
- Plate positioning change
- Press fit
- Product changeover
- Product test simulations
- Robot manipulator arms
- Sonic welding
- Sorting
- Table positioning
- Tension control
- Test stands
- Volumetric pumps
- Web guidance
- Wire winding

CONTENTS

What is the ERD . . . . . ERD_2
Rod-Style Actuators . . . ERD_2
Applications . . . . . ERD_3
FEATURES
ERD . . . . . ERD_4
ERD SS . . . . . ERD_6
SPECIFICATIONS
ERD . . . . . ERD_7
PERFORMANCE
ERD . . . . . ERD_9
GD2. . . . . ERD_11
DIMENSIONS
Actuator . . . . . ERD_13
Options: IP67, FFG . . . ERD_14
SRE, CLV, ALC . . . . . ERD_15
FM2, ... ERD_16
TRR, PCD. . . . . ERD_17
SS2 . . . . . ERD_18
GD2. . . . . ERD_19
Alternative Motors . . . ERD_20
SWITCHES . . . . . ERD_21
Appl. Data Worksheet ERD_23
Selection Guidelines . . ERD_24
Service Parts . . . . . ERD_25
Ordering. . . . . ERD_26

ERD – ELECTRIC ROD-STYLE ACTUATOR

ENDURANCE TECHNOLOGYSM
A Tolomatic Design Principle

Endurance Technology features are designed for maximum durability to provide extended service life.

The ERD is an economical rod-style electric actuator designed as an alternative to pneumatic cylinders and an option for automating manual processes. The ERD is compatible with many NEMA & metric mount stepper and servo motors to create a flexible, powerful electric actuator solution. Built-to-order in stroke lengths up to 24" (609.6 mm).

MULTIPLE SCREW TECHNOLOGIES

YOU CAN CHOOSE:

- Solid nuts of bronze (15, 20 sizes) offer self locking capability
- Ball nuts offer efficiency, longer life, and higher force capability



THREADED NOSE MOUNT WITH JAM NUT

- Metric threads
- Convenient mounting for many applications (10, 15, 20 sizes)



THREADED ROD END

- Compatible with many commercially available metric rod end accessories
- Standard metric threads
- Male threads

INTERNAL MAGNET

This standard feature accommodates reed and solid state switches anywhere on the main tube

300 SERIES STAINLESS-STEEL MAIN TUBE

300 Series stainless-steel main tube provides high rigidity and corrosion resistance

NOSE BEARING

- Engineered resins for smooth operation
- Provides critical support of thrust rod

STAINLESS-STEEL THRUST TUBE

300 Series stainless-steel thrust tube provides high rigidity and corrosion resistance







YOUR MOTOR HERE® OR NEMA

See page 23 for complete information.

MOTOR ORIENTATION

LMI – Inline

Inline option directly couples the driving shaft and is typically a one-piece housing construction for optimum alignment and support of the motor

RP – Reverse parallel

Reverse-parallel option minimizes the overall length and offers a belt reduction drive with a 1:1 or 2:1 ratio.



OPTIONS

- **INTERNAL ANTI-ROTATE (ARI)**
  Available for 15, 20 sizes only.



- **TRUNNION MOUNT (TRR)**
  For applications that require pivoting, 300 series stainless steel construction. Available on all sizes



- **REAR CLEVIS MOUNT (PCD)**
  For applications that require rear pivot, (Available for 15, 20 sizes with RP mounting only)



- **FOOT MOUNT (FM2)***
  For applications that require bottom mounting, 300 series stainless steel construction. Available on all sizes



- **FRONT FLANGE MOUNT (FFG)***
  For front mounting applications, 300 series stainless steel construction. Available on all sizes



- **SWITCHES***
  Choose from: Reed, Solid State PNP or NPN, all available in normally open. Available on all sizes

***NOTE: Foot Mount, Front Flange Mount and Switches are shipped together with the actuator but are not installed by Tolomatic.**

- **GUIDE (GD2)**
  For applications that require anti-rotation, or guidance and load bearing. Tooling plate and guide block made of lightweight aluminum and high performance polymer bearings. Available on all sizes.



INTEGRAL GUIDE RODS AND BEARINGS

- Stainless-steel guide rods provide high rigidity and low deflection
- Four composite bearings support the load for smooth consistent motion

SS HYGIENIC OPTION

ALL 300 SERIES STAINLESS STEEL, IP69K

The all 300 series stainless-steel ERD incorporates hygienic design principles. With an IP69K rating ERD-SS actuators are built-to-order in stroke lengths up to 0.6 m (24").

ENDURANCE TECHNOLOGYSM
A Tolomatic Design Principle

Endurance Technology features are designed for maximum durability to provide extended service life.

SS2 ENCLOSED MOTOR DESIGN



- Features protective enclosure for stepper/servo motors.
- IP69K rating (static).
- Contact Tolomatic for available motors

SS1 OPTION ACTUATOR



IP69K RATED

- To withstand high-pressure wash-down
- Clean-in-place compatible

ALL 300 SERIES STAINLESS STEEL CONSTRUCTION

- 300 series stainless steel for corrosion resistance
- Simplifies and lowers cost of machine design by eliminating the need for protective guards around standard actuators

SMOOTH EXTERIOR

This primary design decision eases cleanup and helps to prevent bacterial growth

DURABLE SEALS

Polyurethane for IP69K ingress protection and resistance to caustic wash-down

STAINLESS STEEL FASTENERS

- Standard metric threads
- Hex fasteners for sturdy construction without potential particle collection areas

THREADED ROD END

- Compatible with many commercially available metric rod end accessories
- Standard metric threads
- Male threads



NOTE: ERD22, ERD25, ERD30 ARE REPLACED BY THE IMPROVED DESIGN OF THE RSH22, RSH25, RSH30

ERD – Electric Rod-Style Actuator

SIZE: **ALL**

SPECIFICATIONS

sizeit.tolomatic.com for fast, accurate actuator selection

SPECIFICATIONS (US conventional measurement)

ERD SIZE*	MAXIMUM STROKE**	SCREW CODE	LEAD	LEAD ACCURACY	BACKLASH	MAXIMUM THRUST	DYNAMIC LOAD RATING	INERTIA		
								LMI	RP	
								Base	Base	Per Inch
	in		in/rev	in/ft	in	lbf	lbf	lb-in^2	lb-in^2	lb-in^2
10	10	BNM05	0.197	0.004	0.005	100	240	0.0040	–	0.0014
15	24	BNM05	0.197	0.004	0.005	200	450	0.0178	0.2208	0.0044
		BNM10	0.394	0.004	0.005	200	400	0.0178	0.2208	0.0044
		BZ10	0.100	0.006	0.008	200	NA	0.0178	0.2208	0.0044
20	24	BNM05	0.197	0.004	0.005	500	900	0.0628	0.4102	0.0263
		BNM10	0.394	0.004	0.005	500	900	0.0628	0.4102	0.0263
		BNM20	0.788	0.004	0.004	500	2,248	0.0628	0.4102	0.0105
		BZ10	0.100	0.006	0.008	500	NA	0.0628	0.4102	0.0105

SPECIFICATIONS (metric measurement)

ERD SIZE*	MAXIMUM STROKE**	SCREW CODE	LEAD	LEAD ACCURACY	BACKLASH	MAXIMUM THRUST	DYNAMIC LOAD RATING	INERTIA		
								LMI	RP	
								Base	Base	Per 25mm
	mm		*mm/rev*	*mm/300mm*	*mm*	*N*	*N*	*kg-m^2 x 10^{-6}*	*kg-m^2 x 10^{-6}*	*kg-m^2 x 10^{-6}*
10	254.0	BNM05	5.00	0.10	0.13	445	1,068	1.16	–	0.41
15	609.6	BNM05	5.00	0.10	0.13	890	2,002	5.21	64.61	1.28
		BNM10	10.00	0.10	0.13	890	1,779	5.21	64.61	1.28
		BZ10	2.54	0.15	0.20	890	NA	5.21	64.61	1.28
20	609.6	BNM05	5.00	0.10	0.13	2,224	4,003	18.38	120.04	7.70
		BNM10	10.00	0.10	0.13	2,224	4,003	18.38	120.04	7.70
		BNM20	20.00	0.10	0.10	2,224	10,000	18.38	120.04	3.07
		BZ10	2.54	0.15	0.20	2,224	NA	18.38	120.04	3.07

*ERD22, ERD25, ERD30 are replaced by the improved design of the RSH22, RSH25, RSH30
**Longer stroke length modification available upon request.

SCREW CODE	DESCRIPTION
BNM	Ball Nut Metric
BZ	Bronze Nut

§Standard Temperature range	40° to 130° F *(4.4° to 54.4° C)*
†**IP** rating	**40** (static) standard for 10, 15, 20 sizes

§Contact Tolomatic to review application for operations outside the standard temperature range.

†IP67 & IP69K hygienic actuators available

SIDE LOAD CONSIDERATIONS

The standard ERD rod-style actuator is not meant to be used in applications where side loading occurs. If side loading exists in the application consider the GD2 guided option.

Loads must be guided and supported. Loads should be aligned with the line of motion of the thrust rod.

Side loading will affect the life of the actuator.



SPECIFICATIONS (US conventional measurement)

ERD SIZE*	MAXIMUM STROKE**	SCREW CODE	WEIGHT					WEIGHT (GD2 adder)	
			LMI (AL)	RP (AL)	RP (SS)	(SS2 adder)			
			Base	Base	Base	Base	Per Inch	Base	Per Inch
	in		lb	lb	lb	lb	lb	lb	lb
10	10	BNM05	0.607	–	–	2.280	0.087	1.028	0.061
15	24	BNM05	1.170	4.230	7.761	5.771	0.159	2.297	0.095
		BNM10	1.170	4.230	7.761	5.771	0.159	2.297	0.095
		BZ10	1.170	4.230	7.761	5.771	0.159	2.297	0.095
20	24	BNM05	7.575	23 FRM 5.610 34 FRM 6.050	23 FRM 9.030 34 FRM 9.448	7.552	0.325	6.455	0.256
		BNM10	7.575			7.552	0.325	6.455	0.256
		BNM20	7.575			7.552	0.325	6.455	0.256
		BZ10	7.575			7.552	0.325	6.455	0.256

SPECIFICATIONS (metric measurement)

ERD SIZE*	MAXIMUM STROKE**	SCREW CODE	WEIGHT					WEIGHT (GD2 adder)	
			LMI (AL)	RP (AL)	RP (SS)	(SS2 adder)			
			Base	Base	Base	Base	Per 25mm	Base	Per Inch
	mm		*kg*	*kg*	*kg*	*kg*	*kg*	*kg*	*kg*
10	254.0	BNM05	0.275	–	–	1.034	0.039	0.466	0.028
15	609.6	BNM05	0.531	1.919	3.520	2.618	0.072	1.042	0.043
		BNM10	0.531	1.919	3.520	2.618	0.072	1.042	0.043
		BZ10	0.531	1.919	3.520	2.618	0.072	1.042	0.043
20	609.6	BNM05	3.436	23 FRM 2.545 34 FRM 2.744	23 FRM 4.096 34 FRM 4.286	3.426	0.147	2.928	0.116
		BNM10	3.436			3.426	0.147	2.928	0.116
		BNM20	3.436			3.426	0.147	2.928	0.116
		BZ10	3.436			3.426	0.147	2.928	0.116

*ERD22, ERD25, ERD30 are replaced by the improved design of the RSH22, RSH25, RSH30
**Longer stroke length modification available upon request.

SCREW CODE	DESCRIPTION
BNM	Ball Nut Metric
BZ	Bronze Nut

ERD – Electric Rod-Style Actuator

SIZE: **ALL**

PERFORMANCE

sizeit.tolomatic.com for fast, accurate actuator selection

CRITICAL SPEED CAPACITY



PV LIMITS



PV LIMITS: Any material which carries a sliding load is limited by heat buildup. The factors that affect heat generation rate in an application are the pressure on the nut in pounds per square inch and the surface velocity in feet per minute. The product of these factors provides a measure of the severity of an application.

(Pressure Velocity of Acme Nut)

P x V ≤ 0.1

$$\left(\frac{\text{Thrust}}{\text{(Max. Thrust Rating)}}\right) \times \left(\frac{\text{Speed}}{\text{(Max. Speed Rating)}}\right) \leq 0.1$$

SCREW LIFE (BALL NUTS)



NOTE: The **L_{10}** *expected life of a ball screw linear actuator is expressed as the linear travel distance that 90% of properly maintained ball screw manufactured are expected to meet or exceed. This is not a guarantee and this graph should be used for estimation purposes only.*

The underlying formula that defines this value is:

$$L_{10} = \left(\frac{C}{P_e}\right)^3 \bullet \ell \equiv$$

L_{10}Travel life in millions of units (in or mm), where:

C = Dynamic load rating (lbf) or *(N)*
P_e = Equivalent load (lbf) or *(N)*
If load is constant across all movements then:
actual load = equivalent load
ℓ = Screw lead (in/rev) *(mm/rev)*

*Use the "**Equivalent Load**" calculation below, when the load is not constant throughout the entire stroke. In cases where there is only minor variation in loading, use greatest load for life calculations.*

Where:

$$P_e = \sqrt[3]{\frac{L_1(P_1)^3 + L_2(P_2)^3 + L_3(P_3)^3 + L_n(P_n)^3}{L}}$$

P_e = Equivalent load (lbf) or *(N)*
P_n = Each increment at different load (lbf) or *(N)*
L = Total distanced traveled per cycle (extend + retract stroke)
[$L = L_1 + L_2 + L_3 + L_n$]
L_n = Each increment of stroke at different load (in) or *(mm)*

ERD – Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection

OPTION: **GD2 – GUIDED ERD** **SPECIFICATIONS**

LOAD VS EXTENDED LENGTH



10, 15



15, 20



BENDING MOMENTS

10, 15



15, 20



USE THE TOLOMATIC SIZING AND SELECTION SOFTWARE AVAILABLE ON-LINE AT www.tolomatic.com OR... CALL TOLOMATIC AT 1-800-328-2174. We will provide any assistance needed to determine the proper actuator for the job.

GUIDE ROD DEFLECTION

10



NOTE: Deflection is measured at the tooling plate. Excessive deflection may impact actuator life. Contact Tolomatic for assistance



15



20



What is an IP Rating?
The IP Code (or Ingress Protection Rating) consists of the letters IP followed by two digits and an optional letter. As defined in international standard IEC 60529, it classifies the degrees of protection provided against the intrusion of solid objects (including body parts like hands and fingers), dust, accidental contact, and water in electrical enclosures.

The IP69K test specifies a spray nozzle that is fed with 80°C water at 8–10MPa (80–100bar) and a flow rate of 14–16L/min. The nozzle is held 10–5 cm from the tested device at angles of 0°, 30°, 60° and 90° for 30s each. The test device sits on a turntable that rotates once every 12s (5rpm).

SOLIDS, FIRST DIGIT:		
4	>1 mm	Most wires, screws, etc.
6	Dust tight	No ingress of dust; complete protection against solid object intrusion
LIQUIDS, SECOND DIGIT (static rating)		
0	Not protected	
7	Immersion up to 1 m	Ingress of water in harmful quantity shall not be possible when the enclosure is immersed in water under defined conditions of pressure and time (up to 1 m of submersion).
9K	High pressure, high temp. wash-down	As above, plus ingress of water in harmful quantity shall not be possible when the enclosure is subject to high pressure, high temperature wash-down.

What Does IP69K mean?
German standard DIN 40050-9 extends the IEC 60529 rating system described above with an IP69K rating for high-pressure, high-temperature wash-down applications.[4] Such enclosures must not only be dust tight (IP6X), but also able to withstand high-pressure and steam cleaning.

The first digit indicates the level of protection that the enclosure provides against access to hazardous parts (e.g., electrical conductors, moving parts) and the ingress of solid foreign objects.

The second digit indicates the level of protection that the enclosure provides against harmful ingress of water.

ERD – Electric Rod-Style Actuator

SIZE: **10, 15, 20**

DIMENSIONS

tolomatic.com/CAD
Download 3D CAD
Always use CAD solid model to determine critical dimensions

ACTUATOR



See page 19 for RP case dimensions.
(Always use configurated CAD solid model for critical dimensions.)

	ERD10	ERD15	ERD20
A	40.13	56.39*	★
B	Ø43.82	Ø66.68*	★
C	-	M4 x 0.7*	★
D	Ø3.91	-	★
E	18.80	21.59*	★
F	106.7	137.2*	★
G	12.70	15.24	18.75
H	3.89	3.89	3.89
I	12.70	19.05	19.05
J**	M8 x 1.25	M12 x 1.75	M16 x 2.0
K	Ø17.42	Ø26.40	Ø33.60

	ERD10	ERD15	ERD20
L	M24 x 1.5	M34 x 1.5	M44 x 1.5
II	6.00	8.00	8.00
M	Ø26.42	Ø41.61	Ø52.20
N	2.50	2.50*	★
O	13.00	13.00	23.37
P	8.20	7.57*	★
Q	(2) M6 x 1.0 ↧7.9	(2) M6 x 1.0 ↧12.7	(2) M6 x 1.0 ↧12.7
R	Ø5.00	Ø6.35*	★
S	27.94	31.75*	★

Dimensions in millimeters

sizeit.tolomatic.com
for fast, accurate actuator selection

tolomatic.com/ask
Technical support before and after purchase

	ERD10	ERD15	ERD20
A	*1.580*	*2.220**	★
B	*Ø1.725*	*Ø2.625**	★
C	-	M4 x 0.7*	★
D	*Ø.154*	-	★
E	*0.740*	*0.850**	★
F	*4.20*	*5.40**	★
G	*0.500*	*0.600*	*0.750*
H	*0.153*	*0.153*	*0.153*
I	*0.500*	*0.750*	*0.750*
J**	M8 x 1.25	M12 x 1.75	M16 x 2.0
K	*Ø.686*	*Ø1.041*	*Ø1.323*

	ERD10	ERD15	ERD20
L	M24 x 1.5	M34 x 1.5	M44 x 1.5
II	*0.236*	*0.315*	*0.315*
M	*Ø1.040*	*Ø1.638*	*Ø2.051*
N	*0.098*	*0.098**	★
O	*0.512*	*0.512*	*0.920*
P	*0.323*	*0.298**	★
Q	*(2) M6 x 1.0 ↧.31*	*(2) M6 x 1.0 ↧.50*	*(2) M6 x 1.0 ↧.50*
R	*Ø.197*	*Ø.250**	★
S	*1.100*	*1.250**	★

Dimensions in inches

*This dimension is determined by motor choice.
** Note: If ordering as a replacement actuator for use with rod end options, order Code RA1 to receive M10x1.25 rod end thread on the ERD15
Note: If ordering as a replacement actuator for use with rod end options, order Code RA1 to receive M16x1.5 rod end thread on the ERD20

ERD – Electric Rod-Style Actuator

SIZE: **10, 15, 20**

DIMENSIONS

tolomatic.com/CAD
Download 3D CAD
Always use CAD solid model to determine critical dimensions

IP67 - IP69K OPTION DIMENSIONS



IP67 (static rating) option replaces the Jam Nut (II in table for standard ERD actuator)

IP67 OPTION

	ERD10	ERD15	ERD20
F	121.8	152.4*	204.8*
G	44.17	53.0	72.5
I	Surface for mounting options		

IP69K OPTION

	ERD10	ERD15	ERD20
F	128.1	164.8	204.8*
G	50.52	65.7	72.5
I	Surface for mounting options		

Dimensions in millimeters

IP67 OPTION

	ERD10	ERD15	ERD20
F	*4.79*	*6.00**	*8.06**
G	*1.739*	*2.09*	*2.85*
I	Surface for mounting options		

IP69K OPTION

	ERD10	ERD15	ERD20
F	*5.04*	*6.49*	*8.06**
G	*1.989*	*2.59*	*2.85*
I	Surface for mounting options		

Dimensions in inches

sizeit.tolomatic.com
for fast, accurate actuator selection

*Dimension shown is with Tolomatic AMS1xx motor hardware YMH option will determine this dimension.

FFG - FRONT FLANGE*



	ERD10	ERD15	ERD20
A	57.15	63.50	88.90
B	34.93	44.45	57.15
C	22.23	31.75	44.45
D	44.45	50.80	76.20
E	Ø4.93	Ø5.61	Ø7.14
F	28.00	40.00	48.08
G	4.93	4.93	4.93
H	6.00	8.00	8.00

Dimensions in millimeters

	ERD10	ERD15	ERD20
A	*2.250*	*2.500*	*3.500*
B	*1.375*	*1.750*	*2.250*
C	*0.875*	*1.250*	*1.750*
D	*1.750*	*2.000*	*3.000*
E	*Ø.194*	*Ø.221*	*Ø.281*
F	*1.102*	*1.575*	*1.890*
G	*0.194*	*0.194*	*0.194*
H	*0.236*	*0.315*	*0.315*

Dimensions in inches

tolomatic.com/ask
Technical support before and after purchase

*The FFG option for the ERD Sizes 10, 15, and 20 comes loosely tightened from Tolomatic to allow for ease of installation in the field. The Jam Nut must be tightened after ERD installation according to the procedure in ERD Parts Sheet 2190-4001

ERD – Electric Rod-Style Actuator

SIZE: **10, 15, 20**

DIMENSIONS

tolomatic.com/CAD
Download 3D CAD
Always use CAD solid model to determine critical dimensions

SRE SPHERICAL ROD END





Allows for slight misalignment between the load and the actuator (radial and angular). Uses an industry-standard bearing.

Size	A Ø	B	C	D	E	F Ø	G	H
10	22.3	36.0	12.0	8.8	10°	8.0	M8x1.25	17.0
15	28.0	43.0	14.0	10.5	10°	10.0	M10x1.25	20.0
20	42.0	64.0	21.0	15.0	10°	16.0	M16x1.5	28.0

Dimensions in millimeters

Size	A Ø	B	C	D	E	F Ø	G	H
10	*0.88*	*1.42*	*0.47*	*0.34*	*10°*	*0.31*	*M8x1.25*	*0.67*
15	*1.10*	*1.69*	*0.55*	*0.41*	*10°*	*0.39*	*M10x1.25*	*0.79*
20	*1.65*	*2.52*	*0.83*	*0.59*	*10°*	*0.63*	*M16x1.5*	*1.10*

Dimensions in inches

CLV CLEVIS ROD END





Used with the externally threaded rod end when the actuator has to compensate for misalignment or pivot about an axis.

Size	A Ø	B	C	D	E	F	G
10	8.0	8.0	16.0	16.0	10.0	32.0	M8x1.25
15	10.0	10.0	20.0	20.0	12.0	40.0	M10x1.25
20	16.0	16.0	32.0	32.0	19.0	64.0	M16x1.5

Dimensions in millimeters

Size	A Ø	B	C	D	E	F	G
10	0.32	0.32	0.63	0.63	0.39	1.26	M8x1.25
15	0.39	0.39	0.79	0.79	0.47	1.57	M10x1.25
20	0.63	0.63	1.26	1.26	0.75	2.52	M16x1.5

Dimensions in inches

* Note: ERD15 rod end options use M10 X1.25 thread, not the standard M12 X 1.75 rod end thread. When ordering an attachment with the actuator the actuator will come with M10x1.25 thread.
Note: ERD20 rod end options use M16 X1.5 thread, not the standard M16 X 2.0 rod end thread. When ordering an attachment with the actuator the actuator will come with M16x1.5 thread.

ALC ALIGNMENT COUPLER





Used in combination with the externally threaded rod end to provide smooth motion and extends actuator life by preventing binding caused by angular or axial misalignment. Not available for use with clevis or trunnion mounts, as they must be rigidly mounted.



Size	A	B	C	D	E	F
15	6.0	M10x1.25	20.0	73.0	30.0	32.0
20	8.0	M16x1.5	32.0	108.0	41.0	45.0

Dimensions in millimeters

Size	A	B	C	D	E	F
15	*0.24*	*M10x1.25*	*0.79*	*2.87*	*1.18*	*1.26*
20	*0.31*	*M16x1.5*	*1.26*	*4.25*	*1.61*	*1.77*

Dimensions in inches

Note: ERD15 rod end options use M10 X1.25 thread, not the standard M12 X 1.75 rod end thread. When ordering an attachment with the actuator the actuator will come with M10x1.25 thread.
Note: ERD20 rod end options use M16 X1.5 thread, not the standard M16 X 2.0 rod end thread. When ordering an attachment with the actuator the actuator will come with M16x1.5 thread.

ERD – Electric Rod-Style Actuator

SIZE: **10, 15, 20**

DIMENSIONS

tolomatic.com/CAD
Download 3D CAD
Always use CAD solid model to determine critical dimensions

FM2 - FOOT MOUNT



	ERD10	ERD15	ERD20	BNM20
J	8.20	7.57	—	—
K	7.82	10.31	14.46	—
L	50.80	66.04	82.55	—
M	59.87	80.39	81.28	109.86
N	25.4	31.75	31.75	—
P	Ø4.93	Ø5.61	Ø7.14	—
K-RP	—	13.11	12.70	—
L-RP	—	88.90	93.35	—
M-RP	—	77.15	66.95	95.53

Dimensions in millimeters

	ERD10	ERD15	ERD20	BNM20
J	*0.323*	*0.298*	—	—
K	*0.308*	*0.406*	*0.569*	—
L	*2.00*	*2.600*	*3.250*	—
M	*2.357*	*3.165*	*3.200*	*4.325*
N	*1.00*	*1.250*	*1.25*	—
P	*Ø.194*	*Ø.221*	*Ø.281*	—
K-RP	—	*0.516*	*0.500*	—
L-RP	—	*3.500*	*3.675*	—
M-RP	—	*3.038*	*2.636*	*3.761*

Dimensions in inches

sizeit.tolomatic.com
for fast, accurate actuator selection

sizeit.tolomatic.com for fast, accurate actuator selection
or call Tolomatic (1-800-328-2174) with application information. We will provide any assistance needed to determine the proper actuator.

tolomatic.com/ask
Technical support before and after purchase

ERD – Electric Rod-Style Actuator

SIZE: **10, 15, 20**

DIMENSIONS

tolomatic.com/CAD
Download 3D CAD
Always use CAD solid model to determine critical dimensions

TRM / TRR - TRUNNION MOUNT



*Dimension is variable dependent on YMH motor code.

TRM	ERD15	ERD20
ØA2	Ø12.000 +0.018 -0.007	Ø16.00 / Ø15.98
ØA3	Ø11.987 / Ø11.975	Ø15.98 / Ø15.95
B2	10.9	19.1
B3	12.7	16.0
C2	10.8	10.8
D3	93.4	94.7
F3	123.3	136.4
F3 (BNM20)	–	165.1

Dimensions in millimeters

PCD - REAR CLEVIS (RP)



TRM	ERD10	ERD15	ERD20
ØA1	Ø8.000 +0.015 -0.006	Ø12.000 +0.005 0.000	Ø15.997 Ø15.982
B1	6.4	10.9	19.0
C1	9.9	10.8	25.1
D1	40.1	56.4	60.0

Dimensions in millimeters

TRR	ERD10	ERD15	ERD20
ØA1	*Ø.2500 +0.0002 0.0000*	*Ø.375 +0.0007 +0.0003*	*Ø.6245 Ø.6240*
B1	*0.25*	*0.43*	*0.75*
C1	*0.39*	*0.43*	*0.99*
D1	*1.58*	*2.22*	*2.36*

Dimensions in inches

TRR	ERD15	ERD20
ØA2	*Ø.3750 +0.0002 -0.0000*	*Ø.6245 / Ø.6240*
ØA3	*Ø.4719 / Ø.4714*	*Ø.629/ Ø.628*
B2	*0.43*	*0.75*
B3	*0.50*	*0.63*
C2	*0.43*	*0.42*
D3	*3.68*	*3.73*
F3	*4.85*	*5.37*
F3 (BNM20)	–	*6.50*

Dimensions in inches

	15		20	
	PCD1	PCD2	PCD1	PCD2
U SML	34.93	34.93	34.93	34.93
U LRG	--	--	34.93	34.93
V	25.40	24.00	25.40	24.00
W	21.56	21.56	21.59	21.59
X	34.26	33.55	34.29	33.58
Y	19.05	27.99	19.05	27.99
Z	12.687 / 12.675	11.99 / 11.97	12.687 / 12.675	11.99 / 11.97
AA SML	69.85	69.85	69.85	69.85
AA LRG	--	--	100.33	100.33
BB	--	--	69.85	69.85
CC SML	142.37	142.37	142.37	142.37
CC LRG	--	--	175.39	175.39
DD SML	58.72	58.72	62.36	62.36
DD LRG	--	--	62.99	62.99
EE	63.40	63.40	63.40	63.40
GG	--	--	59.82	59.82

Dimensions in millimeters

	15		20	
	PCD1	PCD2	PCD1	PCD2
U SML	*1.375*	*1.375*	*1.375*	*1.375*
U LRG	--	--	*1.375*	*1.375*
V	*1.000*	*0.945*	*1.000*	*0.945*
W	*0.849*	*0.849*	*0.850*	*0.850*
X	*1.349*	*1.321*	*1.350*	*1.322*
Y	*0.750*	*1.102*	*0.750*	*1.102*
Z	*.4995 / .4990*	*.4719 / .4714*	*.4995 / .4990*	*.4719 / .4714*
AA SML	*2.750*	*2.750*	*2.750*	*2.750*
AA LRG	--	--	*3.950*	*3.950*
BB	--	--	*2.750*	*2.750*
CC SML	*5.605*	*5.605*	*5.605*	*5.605*
CC LRG	--	--	*6.905*	*6.905*
DD SML	*2.312*	*2.312*	*2.455*	*2.455*
DD LRG	--	--	*2.480*	*2.480*
EE	*2.496*	*2.496*	*2.496*	*2.496*
GG	--	--	*2.355*	*2.355*

Dimensions in inches

ERD – Electric Rod-Style Actuator

SIZE: **10, 15, 20**

DIMENSIONS

tolomatic.com/CAD
Download 3D CAD
Always use CAD solid model to determine critical dimensions

SS2 – STAINLESS-STEEL BODY WITH PROTECTIVE MOTOR COVER AND IP69K UPGRADE



	ERD10	ERD15	ERD20	BNM20
A	204.0	282.70	311.4	339.98
B	26.42	41.61	52.10	
C	24.00	24.00	24.00	
D	65.10	89.00	89.00	
E	4.39	5.27	5.27	
F	100.99	134.98	171.64	
G	113.56	143.76	164.80	193.37
H	44.17	53.04	72.48	
J*	M6 x 1.0	M6 x 1.0	M6 x 1.0	
K	13.00	13.00	23.37	
L	Surface for mounting options			

Dimensions in millimeters

	ERD10	ERD15	ERD20	BNM20
A	*8.03*	*11.130*	*12.26*	*13.385*
B	*1.040*	*1.638*	*2.051*	
C	*0.945*	*0.945*	*0.945*	
D	*2.563*	*3.504*	*3.504*	
E	*0.173*	*0.207*	*0.207*	
F	*3.976*	*5.314*	*6.758*	
G	*4.471*	*5.660*	*6.488*	*7.613*
H	*1.739*	*2.088*	*2.853*	
J*	M6 x 1.0	M6 x 1.0	M6 x 1.0	
K	*0.512*	*0.512*	*0.920*	
L	Surface for mounting options			

Dimensions in inches

	Code	Encoder Code	Available cable exit options:
M	SS21	G1,E1	no cord grips 1/2" NPT tapped hole
	SS22	G1,E1	no cord grips M20 x 1.5 tapped hole
	SS23	G1	1 cord grip (motor, no encoder)
		E1	2 cord grips (motor, with encoder)

*Unit ships standard with hex bolts in these tapped holes

sizeit.tolomatic.com
for fast, accurate actuator selection

sizeit.tolomatic.com for fast, accurate actuator selection or call Tolomatic (1-800-328-2174) with application information. We will provide any assistance needed to determine the proper actuator.

tolomatic.com/ask
Technical support before and after purchase

ERD – Electric Rod-Style Actuator

SIZE: **10, 15, 20**

DIMENSIONS

tolomatic.com/CAD
Download 3D CAD
Always use CAD solid model to determine critical dimensions

GD2 – GUIDED ERD



ERD20 requires minimum 40mm of stroke for GD2 option

GUIDED ERD WITH IP67 OPTION
ERD STROKE IS REDUCED BY DIMENSION "V"

	ERD10	ERD15	ERD20
A	88.90	114.30	149.86
B	50.80	63.50	82.55
C	31.75	47.63	63.50
D	25.40	25.40	50.8
EØ	5.61	7.14	8.74
	⌴9.7 x 5.6↧	⌴11.2 x 7.1↧	⌴13.5 x 8.6↧
FØ	9.53	12.70	19.05
G	40.13	56.39*	*
H	69.85	88.90	117.48
J	25.40	25.40	38.10
K	107.80	137.87*	*
L	50.80	63.50	127.00
M	15.88	22.23	25.40
N	40.13	56.39	60.96
P	38.10	50.80	58.42
R	25.40	38.10	38.10
S	M5x0.8	M6x1.0	M8x1.25
T	76.20	101.60	127.00
U	34.93	44.45	57.15
V	14.91	14.86	30.47

Dimensions in millimeters

	ERD10	ERD15	ERD20
A	*3.500*	*4.500*	*5.900*
B	*2.000*	*2.500*	*3.250*
C	*1.250*	*1.875*	*2.500*
D	*1.000*	*1.000*	*2.00*
EØ	*0.221*	*0.281*	*0.344*
	⌴*0.38 x 0.22*↧	⌴*0.44 x 0.28*↧	⌴*0.56 x 0.34*↧
FØ	*0.375*	*0.500*	*0.750*
G	*1.580*	*2.220**	*
H	*2.750*	*3.500*	*4.625*
J	*1.000*	*1.000*	*1.500*
K	*4.244*	*5.428**	*
L	*2.000*	*2.500*	*5.000*
M	*0.625*	*0.875*	*1.000*
N	*1.580*	*2.220*	*2.400*
P	*1.500*	*2.000*	*2.300*
R	*1.000*	*1.500*	*1.500*
S	M5x0.8	M6x1.0	M8x1.25
T	*3.000*	*4.000*	*5.000*
U	*1.375*	*1.750*	*2.250*
V	*0.587*	*0.585*	*1.200*

Dimensions in inches

*This dimension is determined by motor choice.

ERD – Electric Rod-Style Actuator

SIZE: **10, 15**

DIMENSIONS

tolomatic.com/CAD
Download 3D CAD
Always use CAD solid model to determine critical dimensions

ALTERNATIVE MOTOR DIMENSIONS

MOTOR DIMENSIONS – NEMA MOTOR MOUNT

The ERD 10 & 15 sizes are designed to accommodate NEMA standard stepper and servo motors.

ACTUATOR	SIZE
ERD10	NEMA17
ERD15	NEMA23

The only limiting factors are the motor shaft diameter and length. NEMA standard motors from the companies in the table at right have been found to be compatible with the ERD actuator. (*NOT a complete listing)

ERD Compatible NEMA Motor Suppliers*
Anaheim Automation
Animatics
Applied Motion Products
Automation Direct
Cool Muscle
Electrocraft
Fastech
IMS / Scheider Electric
JVL
LIN Engineering
Nippon Pulse Motor
Omega
Oriental Motor
Parker
Sanyo Denki
+ Others

When any motor has been selected for use with the ERD actuator it is important to confirm the motor is compatible with the dimensions in the table below.

				ERD10	ERD15	ERD10	ERD15
MOTOR SHAFT	LENGTH	MIN.	A	12.7	12.7	*0.50*	*0.50*
		MAX.		27.94	31.75	*1.100*	*1.250*
	DIAMETER		B	5.00	6.35	*0.197*	*0.250*
BOLT HOLE	CIRCLE		ØC	43.82	66.68	*1.725*	*2.625*
	SPACING		D	30.99	47.14	*1.220*	*1.856*
MOTOR PILOT	DIAMETER MAX.		E	24.90	39.37	*0.980*	*1.550*
	HEIGHT MAX.		F	3.30	3.30	*0.130*	*0.130*
				Dimensions in millimeters		Dimensions in inches	



MOTOR CHOICES - YOUR MOTOR HERE

SELECT A COMPLETE SYSTEM FROM TOLOMATIC OR ADD ANY MOTION SYSTEM TO OUR ACTUATORS



"YOUR MOTOR HERE" MADE-TO-ORDER MOTOR MOUNTS.

- Select a high-performance Tolomatic electric actuator and we'll provide a motor-specific interface for your motor. With our online database, you can select from over 60 motor manufacturers and hundreds of models.

Visit **www.tolomatic.com/ymh** to find your motor/actuator match!

The ERD 15, 20 sizes utilize Tolomatic's YMH (Your Motor Here) program. See www.tolomatic.com/ymh or consult Tolomatic sales at 1-800-328-2174 for details.

Configure an actuator and a complete motion control system today using Tolomatic's easy-to-use on-line sizing & selection

sizeit.tolomatic.com
for fast, accurate actuator selection

tolomatic.com/ask
Technical support before and after purchase

ERD – Electric Rod-Style Actuator

sizeit.tolomatic.com
for fast, accurate
actuator selection

SWITCHES

SPECIFICATIONS



ERD actuators have 6 switch options: reed, solid state PNP (sourcing) or solid state NPN (sinking); normally open; with flying leads or quick-disconnect.

Commonly used for end-of-stroke positioning, these switches allow clamp-on installation anywhere along the entire actuator length. The internal magnet, located on the thrust tube, is a standard feature. Switches can be installed in the field at any time.

Switches are used to send digital signals to PLC (programmable logic controller), TTL, CMOS circuit or other controller device. Switches contain reverse polarity protection. Solid state QD cables are shielded; shield should be terminated at flying lead end.

All switches are CE rated, IP67 rated and are RoHS compliant. Switches feature bright red or green LED signal indicators.

RoHS COMPLIANT CE

	Order Code	Lead	Switching Logic	Power LED	Signal LED	Operating Voltage	**Power Rating (Watts)	Switching Current (mA max.)	Current Consumption	Voltage Drop	Leakage Current	Temp. Range	Shock / Vibration	IP Rating
REED	RY	5m	SPST Normally Open	—	Red	5 - 240 AC/DC	**10.0	100mA	—	3.0 V max.	—	14 to 158°F [-10 to 70°C]	30 G / 9 G	67
	RK	QD*												
SOLID STATE	TY	5m	PNP (Sourcing) Normally Open	—	Green	5 - 30 VDC	**3.0	200mA	8 mA @ 24V	1.0 V max.	0.01 mA max.		50 G / 9 G	
	TK	QD*												
	KY	5m	NPN (Sinking) Normally Open	—	Red									
	KK	QD*												

*QD = Quick-disconnect Enclosure classification IEC 529 IP67 (NEMA 6) CABLES: Robotic grade, oil resistant polyurethane jacket, PVC insulation

⚠ **WARNING: Do not exceed power rating (Watt = Voltage x Amperage). Permanent damage to sensor will occur.

SWITCH INSTALLATION - FIELD REPLACEMENT INSTRUCTIONS



STEP 1:
Loosen screw and nut.



STEP 2:
Place sensor and wrap the band around the ERD cylinder. Position the hook with the nearest hole on the band and mark the hole with a permanent marker.



STEP 3:
Remove mounting assembly. Cut the band at the nearest edge of the next hole. (The one that's furthest away from the mounting head.)



STEP 4:
Replace the sensor and mounting assembly. Wrap the band and put the chosen hole on the hook. Position the switch and tighten. Tighten nut for steadying.

sizeit.tolomatic.com
for fast, accurate
actuator selection

SWITCHES

WIRING DIAGRAMS





SWITCH DIMENSIONS

☐ Y - direct connect



☐ K - QD (Quick-disconnect) switch





SWITCH CLAMP



APPLICATION DATA WORKSHEET

Fill in known data. Not all information is required for all applications

ORIENTATION

☐ Horizontal



☐ Vertical



☐ Incline °
α _____





☐ Load supported by actuator OR ☐ Load supported by other mechanism

MOVE PROFILE

EXTEND

Move Distance _____
☐ inch (US conventional) ☐ millimeters (Metric)

Move Time _____ **sec**
Max. Speed _____
☐ in/sec ☐ mm/sec

Dwell Time After Move _____ **sec**

RETRACT

Move Distance _____
☐ inch ☐ millimeters

Move Time _____ **sec**
Max. Speed _____
☐ in/sec ☐ mm/sec

Dwell Time After Move _____ **sec**

NO. OF CYCLES _____

☐ per minute ☐ per hour

HOLD POSITION?

☐ **Required**
☐ **Not Required**

☐ After Move ☐ During Power Loss

NOTE: If load or force changes during cycle use the highest numbers for calculations

EXTEND	RETRACT
LOAD _____	**LOAD** _____
☐ lb. (U.S. Standard) ☐ kg. (Metric)	☐ lb. (U.S. Standard) ☐ kg. (Metric)
FORCE _____	**FORCE** _____
☐ lbf. (U.S. Standard) ☐ N (Metric)	☐ lbf. (U.S. Standard) ☐ N (Metric)

STROKE LENGTH _____

☐ inch (US conventional) ☐ millimeters (Metric)

PRECISION

Repeatability _____
☐ inch ☐ millimeters

OPERATING ENVIRONMENT

Temperature, Contamination, Water, etc.

_____
_____
_____

MOTION PROFILE



Graph your most demanding cycle, including accel/decel, velocity and dwell times. You may also want to indicate load variations and I/O changes during the cycle. Label axes with proper scale and units.

CONTACT INFORMATION

Name, Phone, Email
Co. Name, Etc.

_____
_____
_____



sizeit.tolomatic.com
for fast, accurate actuator selection

USE THE TOLOMATIC SIZING AND SELECTION SOFTWARE AVAILABLE ON-LINE AT www.tolomatic.com OR... CALL TOLOMATIC AT 1-800-328-2174.

We will provide any assistance needed to determine the proper actuator for the job.

FAX 1-763-478-8080 **EMAIL help@tolomatic.com**

ERD – Electric Rod-Style Actuator

Selection Guidelines

sizeit.tolomatic.com
for fast, accurate
actuator selection

1 ESTABLISH MOTION PROFILE

Using the application stroke length, desired cycle time, loads and forces, establish the motion profile details including linear velocity and thrust in each of its segments.

2 SELECT ACTUATOR SIZE AND SCREW TYPE

Based on the required velocities and thrust select a size and screw type and lead of the ERD actuator.

3 VERIFY CRITICAL SPEED OF THE SCREW

Verify that the application's peak linear velocity does not exceed the critical speed value for the size and lead of the screw selected.



4 ESTABLISH TOTAL TORQUE REQUIREMENTS

Calculate total system inertia. The peak and RMS torque required from the motor to overcome internal friction, external forces and accelerate/decelerate the load.

5 VERIFY PV VALUE (IF BRONZE)

Verify that the PV value does not exceed the PV value for the size of the screw selected.



6 CALCULATE LIFE (IF BALL SCREW)

Determine the practical load of the system to calculate the L10 estimated life.



7 DETERMINE IF LOAD GUIDANCE IS NEEDED

If application requires carrying a load, anti-rotate, a tooling plate or there is risk of side loading the rod, choose the guided option. (GD2) Available sizes: 10, 15, 20

8 DETERMINE IF INGRESS PROTECTION AGAINST DUST AND WATER IS NEEDED.

If actuator is in contact with dust particulate, water or wash-down environment choose the IP67 or IP69K option.
(IP67) Available sizes: 10, 15, 20;
(IP69K) Available sizes: 10, 15 & 20

9 DETERMINE IF ENVIRONMENT IS CORROSIVE OR WASH DOWN

If corrosion resistance is required for 10-20 sizes, choose from two options of stainless steel components

- (SS1) ERD with all stainless steel components
- (SS2) ERD with all stainless steel components and protective motor enclosure. Contact Tolomatic for available motors.

10 SELECT MOUNTING AND SENSOR CHOICES

Mounting options include: TRR trunnion mount, FFG front flange mount, FM2 foot mount. 6 sensor choices include: reed, solid state PNP or NPN, all in normally open, with flying leads or quick-disconnect couplers.

11 SELECT ACTUATOR CONTROL SOLUTION

Add an extremely easy to use drive and motor combination to power the actuator.

ERD – Electric Rod-Style Actuator



sizeit.tolomatic.com
for fast, accurate
actuator selection

SERVICE PARTS ORDERING

SPECIFICATIONS

ERD ACTUATOR REPLACEMENT KITS

Code	Description	ERD SIZE		
		10	15	20
FFG	Front Flange Mount Kit	2191-1025	2192-1025	2193-1025
FM2	Foot Mount Kit	2191-9001	[1] 2192-9001	[2] 2193-9001
TRR	[3] Trunnion Mount	0610-1044 (order 2)	6000-1785 (order 2)	2193-1018 (order 2)
IP67	[4] IP67 Kit	2191-9201	2192-9201	2193-9201
IP69K	[4] IP69K Kit	–	2192-9221	2193-9202
GD2	Guide Kit	Order via configurator code: GD2ERD_ _ SM _ _ . _ _		

[1] REPLACEMENT ONLY: If ERD15 unit was built with SS2 option, foot mount kit 2192-9203 is required.

[2] REPLACEMENT ONLY: If ERD20 unit was built with RP SS1 option, foot mount kit 2193-9209 is required.

[3] REPLACEMENT ONLY: Trunnion mount option not available with SS2 option

[4] REPLACEMENT ONLY: If used on an actuator that was not originally built with the IP67 option the thrust rod will retract below the Cap/Seal and may damage the seal

Code	Description	ERD SIZE	
		15	20
RA1	*If replacing an actuator with CLV, SRE or ALC rod end option and want to use existing rod end, add **RA1** to the end of the ordering code for thread compatibility. Do not reorder the rod end option.*		

ERD SWITCHES

To order switch kits use configuration code for switch preceded by SW and actuator code.

EXAMPLE: SWERD15KK

KIT	ACTUATOR	SIZE	SWITCH CODE
SW	ERD	15	KK

The example is for 3 Solid State NPN, Normally Open Switches with Quick-disconnect couplers. Each switch is complete with Bracket, Set Screw, Switch and mating QD cable.

Code	Lead	Normally	Sensor Type
RY	5m (197 in)	Open	Reed
RK	Quick-disconnect		
TY	5m (197 in)	Open	Solid State PNP
TK	Quick-disconnect		
KY	5m (197 in)	Open	Solid State NPN
KK	Quick-disconnect		



sizeit.tolomatic.com
for fast, accurate
actuator selection

sizeit.tolomatic.com for fast, accurate actuator selection or call Tolomatic (1-800-328-2174) with application information. We will provide any assistance needed to determine the proper actuator.



tolomatic.com/ask
Technical support
before and after
purchase

ERD – Electric Rod-Style Actuator

sizeit.tolomatic.com for fast, accurate actuator selection

ORDERING

ERD 15 SN02 SM152·4 LMI

OPTION ORDERING

ARI SS1 IP67 FFG KK2 YM___

MODEL

ERD	Rod-Style Actuator

SIZE

10,	**15,**	**20,**

NUT/SCREW COMBINATIONS

SIZE	CODE	TURNS/in (TPI)
10	BNM	05 mm lead
15	BNM	05, 10 mm lead
	BZ	10
20	BNM	05, 10, 20 mm lead
	BZ	10

STROKE LENGTH

SM__._ Enter desired stroke length in millimeters (25.4mm = 1 inch)

MAXIMUM STROKE				
	SN or BN		Roller Nut	
SIZE	*mm*	in	*mm*	in
10	*254.0*	10	–	–
15,20	*609.6*	24	–	–

Contact Tolomatic with requests for longer strokes

MOTOR MOUNTING

LMI	In-line motor mount
RP1*	1:1 ratio, Reverse Parallel motor mount
RP2*	2:1 ratio, Reverse Parallel motor mount

***RP is not available for the 10 size**

Not all codes listed are compatible with all options. Contact Tolomatic with any questions.



NOTE: ERD22, ERD25, ERD30 ARE REPLACED BY THE IMPROVED DESIGN OF THE RSH22, RSH25, RSH30

ACTUATOR GUIDE & ANTI-ROTATE

GD2	Guided unit with 2 guide shafts & tooling plate

Standard GD2 is aluminum body and 300 series stainless shafts even when ordered with SS1

ARI	Internal Anti-Rotate for 15, 20 sizes only

ARI not available for ERD10

ENVIRONMENTAL PROTECTION

SS1	Stainless steel actuator
SS2_*	Stainless steel actuator with protective motor enclosure
SS21	NPT 1/2" conduit thread
SS22	M20x1.5 conduit thread
SS23	Cord grip(s), *1 or 2 grips determined by encoder choice*
IP67 & IP69K	See chart below (IP ratings defined on pg. ERD_9)
LUB	Food grade grease

***NOTE: Contact Tolomatic for motors available with SS2 option**

**SS2 is not available with GD2 option*

NOTE: IP69K available only together with SS1 or SS2 option

ACTUATOR MOUNTING

FFG**	Front Flange Mount
TRM	Trunnion Mounting, Rear (metric)
TRR	Trunnion Mounting, Rear (US standard)
FM2**	Foot Mount
§PCD1	Rear Clevis Mounting inch/ Imperial pin size
§PCD2	Rear Clevis Mounting metric pin size

****NOTE: Foot Mount and Front Flange Mount are shipped together with the actuator but are not installed by Tolomatic.**
§ RP motor mount ONLY: 15, 20 sizes

IP RATING CHOICES AVAILABLE				MOTOR ENCLOSURE AVAILABLE
Size	IP40	IP67	IP69K	
10	Std.	YES	YES	YES
15	Std.	YES	YES	YES
20	Std.	YES	YES	YES

ROD END

Externally threaded rod end is standard

CLV	Clevis Rod End
SRE	Spherical Rod End
ALC	Alignment Coupler Rod End

NOTE: Rod End options above are not available for all ERD sizes. *Stainless steel available for the above rod ends in limited sizes.* **Contact Tolomatic**

For replacement actuator compatible with existing rod end options see RA1 code (previous page)

SWITCHES**

TYPE	LOGIC	NORMALLY	QUICK-DISCONNECT	CODE	QUANTITY	LEAD LENGTH
REED	SPST	Open	No	RY	After code enter quantity desired	5 m (16.4 feet) / 6 in (152mm) to QD connector w/ 5m lead
			Yes	RK		
SOLID STATE	PNP	Open	No	TY		
			Yes	TK		
	NPN	Open	No	KY		
			Yes	KK		

****NOTE: Switches are shipped together with the actuator but are not installed by Tolomatic.**

YOUR MOTOR HERE

YM____	Motor mount for non-Tolomatic motor.

Brakes mounted on reverse parallel motor mounts (especially in vertically positioned actuators) will not prevent back driving of the screw and the load falling under gravity in the event of a timing belt failure. An inline motor mount with a fail-safe brake mounted directly to the actuator shaft or a special geared or thru-shaft reverse parallel construction should be considered if a brake is required in a safety critical application. Contact Tolomatic for alternate reverse parallel brake mounting options.

Gearheads may be used with reverse parallel motor mounts. However, the torque on the belt and internal RP components must remain below the capabilities of the assembly to prevent belt slipping or premature failure. Contact Tolomatic for additional information if required.

AM____	Tolomatic motor: contact factory

Configure an actuator and a complete motion control system today using Tolomatic's easy-to-use on-line sizing & selection

tolomatic.com/ask
Technical support before and after purchase

Tolomatic™

Linear Motion Solutions

ELECTRIC LINEAR ACTUATORS

Rod -Screw-Drive
Rodless Belt-Drive



SERVO LINEAR ACTUATORS

Rod-Style Integrated Motor
ServoWeld



PNEUMATIC LINEAR ACTUATORS

Rodless Band Cylinders
Cable Cylinders



POWER TRANSMISSION

Right Angle Gearboxes
Industrial Caliper Disc Brakes



USA – Headquarters

Tolomatic, Inc.
Hamel MN 55340 USA

763-478-8000
1-800-328-2174
sales@tolomatic.com

tolomatic.com

MÉXICO

Service Center
Querétaro, Mexico
El Marqués, México

+1 (763) 478-8000
help@tolomatic.com

EUROPE

Tolomatic Europe GmbH
Rüsselsheim, Germany

+49 6142 17604-0
help@tolomatic.eu

tolomatic.com/de

CHINA

Tolomatic Automation Products (Suzhou) Co. Ltd.
Suzhou, Jiangsu, China

+86 512 6750 8506
TolomaticChina@tolomatic.com

tolomatic.cn

Learn More About Tolomatic

©2026. All brand and product names are trademarks of their respective owners. Information in this document is believed accurate at time of printing. However, Tolomatic assumes no responsibility for its use or for any errors that may appear in this document. Tolomatic reserves the right to change the design or operation of the equipment described herein and any associated motion products without notice. Information in this document is subject to change without notice.

Visit www.tolomatic.com for the most up-to-date technical information.